



CCT switchable between 3000K, 4000K & 6500K

Grade 316 Coastal protection kit available

BESA mounting kit available

## Caiman CSP 5ft Single

CCT Colour Switchable

### Features

IP rating	IP65
IK rating	IK08
CSP Switchable	Switchable CCT
Sensor Option	On-Off Microwave sensor & daylight switching available
Dimmable Option	Yes (DALI-2, 0-10V)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Self-Test

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 35°C
Weight	1.60Kg
Inrush Current	30A 0.3ms
Construction Material	Anti-UV Polycarbonate
SELV	SELV
Electric Class (1, 2, 3)	1
Suitable for coastal areas	Yes (with modification)
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P

### Guarantee

Warranty	5 years
Battery Warranty	2 years
On-Site Warranty	2 years

### Features & benefits

- IP65 for the highest level of dust protection and able to withstand jets of water from any direction
- 304 stainless steel clips for high corrosion resistance and anti-tamper screws for vandal proofing
- IK08 for robust impact protection
- Unique gear tray slots that allow us to easily integrate third party control gear for your project. Just ask.
- Extended mounting sliders to help make refurbishment easier
- Safety tether cable to gear tray enables fast installation
- Compression cable gland included in fixings kit
- Emergency option available

### Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	EM lm	Energy
AC5SN	Grey RAL7005	Standard	120°	30W	3000K	3450	115	N/A	
					4000K	3900	130	N/A	
					6500K	3750	125		
AC5SNE	Grey RAL7005	Emergency	120°	30W	3000K	3450	115	250lm	
					4000K	3900	130	250lm	
					6500K	3750	125		

### Wiring Information

Cable Required for Connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm <sup>2</sup>
Type of Wiring Required	Parallel

### Accessories

AC5SCLIP316	Coastal application kit	Sold Separately
ACSBESA	BESA mounting kit (indoor only)	Sold Separately
EMBOLTMOPEN	3 hour emergency conversion pack, open area, manual test	Sold Separately
EMBOLTMCOR	3 hour emergency conversion pack, corridor area, manual test	Sold Separately
PIRBOLT	PIR on/off daylight Sensor	Sold Separately

