



CCT switchable between  
3000K, 4000K & 6500K



Grade 316 Coastal  
protection kit available



BESA mounting kit available

## WARRANTY

|                  |         |
|------------------|---------|
| Warranty         | 5 years |
| Battery Warranty | 2 years |
| On-Site Warranty | 2 years |

## FEATURES & BENEFITS

IP65 for the highest level of dust protection and able to withstand jets of water from any direction

304 stainless steel clips for high corrosion resistance and anti-tamper screws for vandal proofing

IK08 for robust impact protection

Unique gear tray slots that allow us to easily integrate third party control gear for your project. Just ask.

Extended mounting sliders to help make refurbishment easier

Safety tether cable to gear tray enables fast installation

Compression cable gland included in fixings kit

Emergency option available

# CAIMAN CSP 5FT TWIN

CCT Colour Switchable

## FEATURES

|                        |  |
|------------------------|--|
| IP rating              | IP65   |
| IK rating              | IK08   |
| CSP Switchable         | Switchable CCT   |
| Sensor Option          | On-Off Microwave sensor & daylight switching available |
| Dimmable Option        | Yes (DALI-2, 0-10V)                                    |
| LED Lifetime           | L70 50,000h  |
| Colour Rendering Index | CRI>80   |
| Colour Consistency     | SDCM4  |
| Emergency Option       | Yes, Self-Test   |

## INSTALLATION INFORMATION

|                             |                         |
|-----------------------------|-------------------------|
| Input                       | 220-240V AC             |
| Maximum Ambient Temperature | -20°C - 35°C            |
| Weight                      | 1.80Kg                  |
| Inrush Current              | 30A 0.3ms               |
| Construction Material       | Anti-UV Polycarbonate   |
| SELV                        | Yes                     |
| Electric Class (1, 2, 3)    | I                       |
| Suitable for coastal areas  | Yes (with modification) |
| Install Connector Type      | Loop in / Loop out      |
| UK Building Regulations     | Part P                  |
| Mounting Options            | Surface                 |
| Power Factor                | 0.9                     |

## Photometrics @ 25°C

| Product Code | Finish       | Type      | Beam | W   | Colour | lm   | lm/W | EM lm | Energy |
|--------------|--------------|-----------|------|-----|--------|------|------|-------|--------|
| AC5TN        | Grey RAL7005 | Standard  | 120° | 50W | 3000K  | 5750 | 115  | -     |        |
|              |              |           |      |     | 4000K  | 6500 | 130  | -     |        |
|              |              |           |      |     | 6500K  | 6250 | 125  | -     |        |
| AC5TNE       | Grey RAL7005 | Emergency | 120° | 50W | 3000K  | 5750 | 115  | 250   |        |
|              |              |           |      |     | 4000K  | 6500 | 130  | 250   |        |
|              |              |           |      |     | 6500K  | 6250 | 125  | -     |        |

## WIRING INFORMATION

|                              |   |
|------------------------------|---|
| Cable Required for Connector | H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm <sup>2</sup> |
| Type of Wiring Required      | Parallel  |

## ACCESSORIES

|            |  |                 |
|------------|--|-----------------|
|            | EMBOLTMOPEN  | Sold Separately |
| EMBOLTMCOR | 3 hour emergency conversion pack, corridor area, manual test | Sold Separately |
| PIRBOLT    | PIR on/off daylight Sensor                                   | Sold Separately |

1545mm 93mm 80mm