





Caiman CSP 6ft Single

Features	
IP rating	IP65
IK rating	IK08
CSP Switchable	Switchable CCT
Sensor Option	On-Off Microwave sensor &
Sensor Option	daylight switching available
Dimmable Option	Yes (DALI-2, 0-10V)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Self-Test

Installation Information				
Input	220-240V AC			
Maximum Ambient Temperature	-20°C - 35°C			
Weight	1.30Kg			
Inrush Current	30A 0.3ms			
Construction Material	Anti-UV Polycarbonate			
SELV	Yes			
Electric Class (1, 2, 3)	1			
Suitable for coastal areas	Yes (with modification)			
Install Connector Type	Loop in / Loop out			
UK Building Regulations	Part P			

Photometrics @ 25°C

Product Code	Finish	Туре	Beam	W	Colour	lm	lm/W	EM lm	Energy			
					3000K	4140	115	-				
AC6SN	Grey RAL7005	Standard	120°	36W	4000K	4680	130	-	A D			
					6500K	4500	125					
	Grey RAL7005 Emergend							3000K	4140	115	250	
AC6SNE		Emergency 120	120°	36W	4000K	4680	130	250	A D			
					6500K	4500	125					

Wiring Information

Cable Required for Connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm²
Type of Wiring Required	Parallel

Accessories

AC6SCLIP316	Coastal application kit	Sold Separately
ACSBESA	BESA mounting kit (indoor only)	Sold Separately
EMBOLTMOPEN	3 hour emergency conversion pack, open area, manual test	Sold Separately
EMBOLTMCOR	3 hour emergency conversion pack, corridor area, manual test	Sold Separately
PIRBOLT	PIR on/off daylight Sensor	Sold Separately

Collingwood



CCT switchable between 3000K, 4000K & 6500K



Grade 316 Coastal protection kit available



BESA mounting kit available

Guarantee

Warranty	5 year
Battery Warranty	2 year
On-Site Warranty	2 year

Features & benefits

- IP65 for the highest level of dust protection and able to withstand jets of water from any direction.
- 304 stainless steel clips for high corrosion resistance and anti-tamper screws for vandal proofing
- IK08 for robust impact protection
- Unique gear tray slots that allow us to easily integrate third party control gear for your project. Just ask.
- Extended mounting sliders to help make refurbishment easier
- Safety tether cable to gear tray enables fast installation
- Compression cable gland included in fixings kit
- Emergency option available

1854mm <u>51mm</u>