Anti-corrosive specification sheet







Yes (with modification)

Loop in / Loop out

Caiman CSP 6ft Single

CCT Colour Switchable

Features				
IP rating	IP65			
IK rating	IK08			
CSP Switchable	Switchable CCT			
S O-+i	On-Off Microwave sensor &			
Sensor Option	daylight switching available			
Dimmable Option	Yes (DALI-2, 0-10V)			
LED Lifetime	L70 50,000h			
Colour Rendering Index	CRI>80			
Colour Consistency	SDCM4			
Emergency Option	Yes, Self-Test			

Installation Information				
Input	220-240V AC			
Maximum Ambient Temperature	-20°C - 35°C			
Weight	1.30Kg			
Inrush Current	30A 0.3ms			
Construction Material	Anti-UV Polycarbonate			
SELV	SELV			
Electric Class (1, 2, 3)	1			

Suitable for coastal areas

Install Connector Type

UK Building Regulations

Photometrics @ 25°C

Product Code	Finish	Туре	Beam	W	Colour	lm	lm/W	EM lm	Energy
					3000K	4140	115	N/A	
AC6SN	Grey RAL7005	Standard	120°	36W	4000K	4680	130	N/A	A D
				650	6500K	4500	125		
					3000K	4140	115	250	
AC6SNE	Grey RAL7005	Emergency	120°	36W	4000K	4680	130	250	A D
			6500K	4500	125				

Wiring Information

Cable Required for Connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm ²		
Type of Wiring Required	Parallel		

Accessories

AC6SCLIP316	Coastal application kit	Sold Separately
ACSBESA	BESA mounting kit (indoor only)	Sold Separately
EMBOLTMOPEN	3 hour emergency conversion pack, open area, manual test	Sold Separately
EMBOLTMCOR	3 hour emergency conversion pack, corridor area, manual test	Sold Separately
PIRBOLT	PIR on/off daylight Sensor	Sold Separately

collingwood



CCT switchable between 3000K, 4000K & 6500K



Grade 316 Coastal protection kit available



BESA mounting kit available

Guarantee

Warranty 5 years Battery Warranty 2 years On-Site Warranty 2 years

Features & benefits

- IP65 for the highest level of dust protection and able to withstand jets of water from
- 304 stainless steel clips for high corrosion resistance and anti-tamper screws for vandal proofing
- IK08 for robust impact protection
- Unique gear tray slots that allow us to easily integrate third party control gear for your project. Just ask.
- Extended mounting sliders to help make refurbishment easier
- Safety tether cable to gear tray enables fast installation
- Compression cable gland included in fixings kit
- Emergency option available