



collingwood



CCT switchable between 3000K, 4000K & 6500K



Grade 316 Coastal protection kit available



BESA mounting kit available



Caiman CSP 6ft Twin

Features

IP rating	IP65
IK rating	IK08
CSP Switchable	Switchable CCT
Sensor Option	On-Off Microwave sensor & daylight switching available
Dimmable Option	Yes (DALI-2, 0-10V)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Self-Test

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 35°C
Weight	2.50Kg
Inrush Current	30A 0.3ms
Construction Material	Anti-UV Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	1
Suitable for coastal areas	Yes (with modification)
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P

Guarantee

Warranty	5 years
Battery Warranty	2 years
On-Site Warranty	2 years

Features & benefits

- IP65 for the highest level of dust protection and able to withstand jets of water from any direction
- 304 stainless steel clips for high corrosion resistance and anti-tamper screws for vandal proofing
- IK08 for robust impact protection
- Unique gear tray slots that allow us to easily integrate third party control gear for your project. Just ask.
- Extended mounting sliders to help make refurbishment easier
- Safety tether cable to gear tray enables fast installation
- Compression cable gland included in fixings kit
- Emergency option available

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	EM lm	Energy
AC6TN	Grey RAL7005	Standard	120°	60W	3000K	6900	115	-	
					4000K	7800	130	-	
					6500K	7500	125	-	
AC6TNE	Grey RAL7005	Emergency	120°	60W	3000K	6900	115	250	
					4000K	7800	130	250	
					6500K	7500	125	-	
AC6TD	Grey RAL7005	DALI-2 dimmable	120°	60W	3000K	6900	115	-	
					4000K	7800	130	-	
					6500K	7500	125	-	
AC6TDE	Grey RAL7005	DALI-2 dimmable	120°	60W	3000K	6900	115	250	
					4000K	7800	130	250	
					6500K	7500	125	-	

Wiring Information

Cable Required for Connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm ²
Type of Wiring Required	Parallel

Accessories

AC6TCLIP316	Coastal application kit	Sold Separately
ACTBESA	BESA mounting kit (indoor only)	Sold Separately
EMBOLTMOPEN	3 hour emergency conversion pack, open area, manual test	Sold Separately
EMBOLTMCOR	3 hour emergency conversion pack, corridor area, manual test	Sold Separately
PIRBOLT	PIR on/off daylight Sensor	Sold Separately

