




CCT switchable between 3000K, 4000K & 5700K



Wattage Switchable



IP66 for external use



CAIMAN QUICK CONNECT

Wire a side mains cable entry without needing to open luminaire (product is through-wired)

FEATURES

IP rating	IP66
IK rating	IK10
CSP Switchable	Switchable CCT
Sensor Option	MW On-Off
Dimmable Option	No
LED Lifetime	L70 100,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 35°C
Weight	1.3 - 2.15kg
Inrush Current	16A 0.51ms
Construction Material	Polycarbonate Housing (RAL7005), Anti-UV Diffuser
SELV	No
Electric Class (1, 2, 3)	I
Install Connector Type	Removeable, moveable, loop in/out
UK Building Regulations	Part L
Mounting Options	Surface
Power Factor	0.9

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	EM Im	Energy
AC4TWN	Grey	4ft (1200mm) Standard	120°	18W	3000K	2590	144	-	AIG C
					4000K	2775	154	-	
					5700K	2775	154	-	
					3000K	5180	144	-	
					4000K	5550	154	-	
					5700K	5550	154	-	
AC5TWN	Grey	5ft (1500mm) Standard	120°	28W	3000K	3920	140	-	AIG C
					4000K	4200	150	-	
					5700K	4200	150	-	
					3000K	7840	140	-	
					4000K	8400	150	-	
					5700K	8400	150	-	
AC6TWN	Grey	6ft (1800mm) Standard	120°	33W	3000K	4690	142	-	AIG C
					4000K	5025	152	-	
					5700K	5025	152	-	
					3000K	9380	140	-	
					4000K	10050	150	-	
					5700K	10050	150	-	

WARRANTY

Warranty	7 years
Battery Warranty	5 years
On-Site Warranty	2 years

FEATURES & BENEFITS

Unique full length mounting slider allows complete freedom of mounting positions

Quick connect through-wired version for side entry to avoid opening the product

Versabox plug and play microwave sensor kit to automate lights off when no presence is detected


Rear and side housing conduit entry points

All installation points are marked on the outside of the luminaire to aid accurate pre-drilling, BESA mount accessory (ACBESA) sold separately


Supplied with mounting clips, hanging bracket and compression glands at either end of luminaire

ACKITMWS must be assembled by Collingwood Production only.

PATENT: **Patent Pending**




600mm (2ft)



1200mm (4ft)



1500mm (5ft)



1800mm (6ft)



92.3mm
73mm

WIRING INFORMATION

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

ACCESSORIES

ACKITMWS	Microwave Sensor on/off Plug-in Kit (Assembled on demand by)	Sold Separately
-----------------	--	-----------------

