





CAIMAN VERSA

CCT Colour & Wattage Switchable Anti-Corrosive with plug-in Versabox accessories

FFATURES

IP rating	IP66	
IK rating	IK10	
CSP Switchable	Switchable CCT	
Sensor Option	Versabox, see accessories	
Dimmehle Ontion	Yes (DALI-2, 0-10V, PUSH-	
Dimmable Option	DIM)	
LED Lifetime	L70 100,000h	
Colour Rendering Index	CRI>80	
Colour Consistency	SDCM6	
F	Yes, Manual, Self and DALI-2	
Emergency Option	Test	

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-25°C to +40°C
Weight	1.33Kg - 1.63Kg
Inrush Current	16A 0.51ms
Construction Material	Polycarbonate Housing
	(RAL7005), Anti-UV Diffuser
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Removeable, moveable,
	loop in/out
UK Building Regulations	Part L
Mounting Options	Surface
Power Factor	0.9

^{*}Replace 'N' at the end of the part code with: 'NEM' for Manual-test Emergency models | 'D' for DALI-2/PUSH DIM | 'V' for 0-10V | Plug in kits also available as separate accessories.

WIRING INFORMATION

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

ACCESSORIES

ACKITMANEM	Manual Test Emergency plug-in Versabox	Sold Separately
ACKITSELFEM	Self Test Emergency plug-in Versabox	Sold Separately
ACKITMWS	Microwave Sensor on/off Plug-in Kit	Sold Separately
ACKITMWSDIM	MIcrowave Sensor Dim plug-in Versabox (requires 0-10V driver)	Sold Separately
ACREMOTEMWS	Remote for Microwave Sensor	Sold Separately
ACBESA	BESA Mounting Bracket	Sold Separately
CASBOLT7W	Casambi Wireless M20 Conduit Entry PIR+DL White 7m (requires 0-10V	Sold Separately
	driver)	



LIGHTING INNOVATION



CCT switchable between 3000K, 4000K & 5700K



Wattage Switchable



IP66 and IK10 for total protection

WARRANTY

7 years

FEATURES & BENEFITS


Versabox plug and play kit range to

Supplied with mounting clips, hanging bracket and compression gland

Quick connect through-wired version for side

DALI-2, 0-10V and DALI Emergency option

PATENT: Patent Pending



92.3mm

1500mm (5ft)

73mm

1800mm (6ft)