
 CCT switchable between 3000K, 4000K & 5700K

 Wattage Switchable

 IP66 and IK10 for total protection

Caiman Versa

CCT Colour & Wattage Switchable Anti-Corrosive with plug-in Versabox accessories

Features

IP rating	IP66
IK rating	IK10
CSP Switchable	Switchable CCT
Sensor Option	Versabox, see accessories
Dimmable Option	Yes (DALI-2, 0-10V, PUSH-DIM)
LED Lifetime	L70 100,000h
Colour Rendering Index	CR>80
Colour Consistency	SDCM6
Emergency Option	Manual, Self & DALI-2 options

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 35°C
Weight	1.3 - 2.15kg
Inrush Current	16A 0.51ms
Construction Material	Polycarbonate Housing (RAL7005), Anti-UV Diffuser
Electric Class (1, 2, 3)	1
Install Connector Type	Removeable, moveable, loop in/out
UK Building Regulations	Part L
Power Factor	0.9

Guarantee

Warranty	7 years
Battery Warranty	5 years
On-Site Warranty	2 years

Features & benefits

- Unique full length mounting slider allows complete freedom of mounting positions
- Versabox plug and play kit range to accommodate project requirements
- Rear and side housing conduit entry points
- Quick release moveable terminal block to suit mains cable entry point
- All installation points marked to aid accurate pre-drilling
- Supplied with mounting clips, hanging bracket and compression gland
- Quick connect through-wired version for side entry also available

Photometrics @ 25°C

Product Code	Type	Beam	W	Colour	lm	lm/W	EM lm	Energy
AC4N	Standard	120°	18W	3000K	2590	144	240	
				4000K	2775	154	240	
				5700K	2775	154	240	
			37W	3000K	5180	144	240	
				4000K	5550	154	240	
AC5N	Standard	120°	28W	3000K	3920	140	230	
				4000K	4200	150	230	
				5700K	4200	150	230	
			56W	3000K	7840	140	230	
				4000K	8400	150	230	
AC6N	Standard	120°	33W	3000K	4690	142	200	
				4000K	5025	152	200	
				5700K	5025	152	200	
			67W	3000K	9380	140	200	
				4000K	10050	150	200	
				5700K	10050	150	200	

*Replace 'N' at the end of the part code with: 'NEM' for Manual-test Emergency models | 'D' for DALI-2/PUSH DIM | 'V' for 0-10V | Plug in kits also available as separate accessories.

Wiring Information

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

Accessories

ACKITMANEM	Manual Test Emergency plug-in Versabox	Sold Separately
ACKITSELFEM	Self Test Emergency plug-in Versabox	Sold Separately
ACKITDALIEM	DALI-2 Emergency plug-in Versabox	Sold Separately
ACKITMWS	Microwave Sensor on/off Plug-in Kit	Sold Separately
ACKITMWSDIM	Microwave Sensor Dim plug-in Versabox (requires 0-10V driver)	Sold Separately
ACREMOEMWS	Remote for Microwave Sensor	Sold Separately
ACBESA	BESA Mounting Bracket	Sold Separately

