



IK10 for protection against high impact



IP65 ideal for car parks and walk ways



PIR sensor included

Cyclo Sensor

Round-terminal PIR bollard

Features

IP rating	IP65
IK rating	IK10
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	5.255kg
Inrush Current	15A @230VAC
Construction Material	Cast Aluminium
UK Bathroom Zone	N/A
SELV	No
Electric Class (1, 2, 3)	1
Earth Leakage	< 250A
Suitable for coastal areas	No

Guarantee

Warranty 5 years

Features & benefits

- Low glare 360° illumination, ideal for pathways, boundary marking, or general illumination of exterior spaces
- 90° PIR sensor, detection area adjustable to 5m max

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
OU516WW24	Anthracite grey RAL7016	600mm	24W	3000K	180°	1660	69	
OU391WW24	Anthracite grey RAL7016	955mm	24W	3000K	180°	1660	69	

Wiring Information

Cable / Flying Lead	Cable
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (driver built in)	220-240V	No	N/A	N/A

Accessories

OU39224	180° Reflector	Sold Separately
---------	----------------	-----------------

