



RGBW



Quick and easy installation
with plug and play
connector



CRI 80 providing true colour
appearance

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Low weight for mounting in ceiling voids

Requires no fan to cool down

Projects light down 1m & 2m lengths of fibre

Separate white LED for permanent use

Compatible with a large range of controllers

DL329RGBW

Colour change fibre optic injector (5W max.)

FEATURES

IP rating	IP20
CSP Switchable	RGBW
Tilttable (°)	Fixed
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	210g
Cut Out Size	N/A
Construction Material	Aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	III
Suitable for coastal areas	No
Install Connector Type	Flying lead

RGBW Photometrics

Product Code	Wattage	Colour	lm	lm/W
DL329RGBW	1.1W	White (4000K)	14	13
DL329RGBW	1W	Red	-	-
DL329RGBW	1.1W	Green	-	-
DL329RGBW	1.1W	Blue	-	-

WIRING INFORMATION

Cable / Flying Lead	2x 1m Plug & Play 5-core ribbon cable
Type of Wiring Required	Series
Input Cable Type	Plug & Play 5 Core ribbon cable

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	13
CCDRV75DMX	220-240V	Yes	Yes	2	13
CCDRV75RF	220-240V	Yes	Yes	2	13

ACCESSORIES

CR575RGBW	5-core PVC cable	Sold Separately
LEDRGBWEXT	Colour change Plug & Play 1m extension lead	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately

