



## H2 LITE CSP

Colour & Wattage Switchable using switches under bezel

### FEATURES

<b>IP rating</b>	IP65 (from below) IP20 (from above)
<b>CSP Switchable</b>	Switchable CCT
<b>Tiltable (°)</b>	Fixed
<b>UGR</b>	UGR<25
<b>Sensor Option</b>	No
<b>Dimmable Option</b>	Yes (Mains)
<b>LED Lifetime</b>	L70 40,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM4
<b>Emergency Option</b>	No
<b>Rotation angle (°)</b>	Fixed

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	40°C
<b>Weight</b>	235g
<b>Insulation Coverable</b>	Rolled and blown insulation
<b>Double Insulation</b>	Yes
<b>Inrush Current</b>	1.8A 0.3ms
<b>Cut Out Size</b>	68-72
<b>Construction Material</b>	Mild steel / V0 rated plastic
<b>UK Bathroom Zone</b>	1
<b>Maximum ceiling thickness</b>	40 mm
<b>SELV</b>	No
<b>Electric Class (1, 2, 3)</b>	II
<b>Suitable for coastal areas</b>	No
<b>Install Connector Type</b>	2 part first fit connector
<b>UK Building Regulations</b>	Part B, C, E, P & L RE2020, EN 13141-1:2004, EN 1365-2:2014, EN ISO 10140-2/3:2010
<b>FR Building Regulations</b>	Solid Timber 30/60/90min, I- Joist 30min, Metal Web 30min
<b>Part B Fire Rating</b>	
<b>Power Factor</b>	0.85



Colour switchable between 2700K, 3000K and 4000K



Wattage switchable between 4.2W & 6W



Switches allow you to choose options at installation

### WARRANTY

Warranty

7 years

### FEATURES & BENEFITS

High efficacy of 124lm/W

2-part connector provides first fix wiring whilst the luminaire is detached from the connector, loop in loop out, quick maintenance should disconnection/reconnection be required

Compatible with Click Flow CT100 series

TRIAC Mains dimmable

Fixed with 55 degree beam angle

Compatible with H2 Twist and lock bezels

When using a converter plate, the IP rating is not affected; however, the product is no longer fire-rated.

PATENT: **GB2461935 GB2475649 GB2481542 EP2350527 NZ592254 HK1153907**

### Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	lx@1m	Energy
DLT551500A	White bezel included	Single unit	55°	4.2W	2700K	450	107	409	
					3000K	520	124	472	
					4000K	500	119	454	
					2700K	625	104	409	
					3000K	720	120	472	
					4000K	700	117	454	
				6W	2700K	625	104	409	
				6W	3000K	720	120	472	
				6W	4000K	700	117	454	

Default Settings: 3000K colour temperature, 6W power consumption. Product not suitable for exterior use, please use H2 Pro Extreme. Energy rating is a reflection of the LED light source.

### WIRING INFORMATION



<b>Cable / Flying Lead</b>	0.75mm <sup>2</sup> - 2.5mm <sup>2</sup> 3 core cable for connector
<b>Cable Required for Connector</b>	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm <sup>2</sup> ) or 3-core cable (R02V 3x1.5mm <sup>2</sup> )
<b>Type of Wiring Required</b>	Parallel

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (intergrated driver)	220-240V	Yes	Yes (mains)	1 (Ceiling only)

### ACCESSORIES

<b>H2 Bezels</b>	Twist and lock bezels	Sold Separately
<b>DLCVT110</b>	Concealer ring for larger cut outs	Sold Separately



<b>DM298FP</b>	Faceplate dimmer	Sold Separately
<b>DM298GRID</b>	Grid dimmer	Sold Separately



**COLLINGWOOD**  
LIGHTING

## LIGHTING INNOVATION

The H2 Lite CSP is a superior solution that is engineered to be the perfect fit-and-forget solution. The colour temperature can be easily controlled by simply twisting the bezel off and flicking the switch on the front face of the product. The addition of the 2700K colour temperature gives you the option of creating an excellent and warm atmosphere. Large piano key terminals allow loop-in/ loop-out wiring with ease.