Downlight accessories specification sheet





DM298GRID

250W LED mains grid dimmer

| Installation Information | |
|--|---|
| Input | 220-240V AC |
| Weight | 50g |
| Construction Material | Plastic |
| UK Bathroom Zone | N/A |
| Case Temperature (tc = °C) | 40 |
| Back box depth | 35mm min |
| California and and annual annu | White adaptors for Hamilton, MK, BG, Crabtree, Schneider, |
| Grid plate adapters | DETA, Hager & Wandsworth grid ranges |
| Dimmer Type | Push on / off, rotary dial dim |
| Load Type | LED dimmable driver only |
| | |

Photometrics @ 25°C

| Product Code | w |
|--------------|-------------------------------|
| DM298GRID | 5W - 250W / 15 LED Units Max. |

Wiring Information

| • | |
|------------------|----------|
| Input Cable Type | 3mm² Max |

Accessories

| Compatible with all Collingwood dimmable products | Sold Separately |
|---|-----------------|
|---|-----------------|



Compatible with many of Collingwood's dimmable downlights

Minimum brightness can be adjusted

Minimum depth of pattress box: 35mm

Guarantee

Warranty 1 year

Features & benefits

- Complete with ring nut and white plastic
- Complete with white plastic grid plates
- BS EN 60669-2-1
- 15 LED units max.





