

# DRV150700

30W CC Driver, IP20, 150-700mA, Class II SELV

# INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	45°C		
Inrush Current	5.38A 0.032ms		
Construction Material	PC		
UK Bathroom Zone	N/A		
SELV	Yes		
Electric Class (1, 2, 3)	II		
Case Temperature (tc = °C)	85		
DIN Rail Mount	No		
Install Connector Type	Push-fit terminals 0,5 - 1,5mm²		
Connection Output	Push-fit terminals		
UK Protection	Open Circuit, Short Circuit, Over Temperature Self Reset		
Power Factor	0.95		

## **Electrical Characteristics**

Driver Rated Wattage	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
30	220-240VAC	150-700mA	2.5-42	0.95



#### LIGHTING INNOVATION

ow 3

Ő

IP**20** 

Quick and easy installation

IP20 Perfect for indoor applications

### WARRANTY

antv

5 years

# FEATURES & BENEFITS

electable drive currents through dip switches :0mA, 250mA, 350mA, 500mA & 700mA electable Settings he ability to select 5 lumen levels without the se of a dimmer river to power Residential Landscape minaires

98mm

# 43mm 22mm

01604 495 151 sales@collingwoodgroup.com collingwoodlighting.com