



## DRV150700

30W CC Driver, IP20, 150-700mA, Class II SELV

### INSTALLATION INFORMATION

|                                    |  |
|------------------------------------|--|
| <b>Input</b>                       | 220-240V AC  |
| <b>Maximum Ambient Temperature</b> | 45°C   |
| <b>Inrush Current</b>              | 5.38A 0.032ms  |
| <b>Construction Material</b>       | PC   |
| <b>UK Bathroom Zone</b>            | N/A  |
| <b>SELV</b>                        | Yes  |
| <b>Electric Class (1, 2, 3)</b>    | 2  |
| <b>Case Temperature (tc = °C)</b>  | 85   |
| <b>DIN Rail Mount</b>              | No   |
| <b>Install Connector Type</b>      | Push-fit terminals 0,5 - 1,5mm <sup>2</sup>              |
| <b>Connection Output</b>           | Push-fit terminals                                       |
| <b>UK Protection</b>               | Open Circuit, Short Circuit, Over Temperature Self Reset |
| <b>Power Factor</b>                | 0.95   |

### Electrical Characteristics

| Driver Rated Wattage | Driver Input Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|----------------------|----------------------|---------------|-----------------------|--------------|
| 30W                  | 150mA-700mA          | 220-240VAC           | 150-700mA     | 2.5-42VDC             | 0.95         |



30W



Quick and easy installation



IP20 Perfect for indoor applications

### WARRANTY

Warranty

5 years

### FEATURES & BENEFITS

Selectable drive currents through dip switches

150mA, 250mA, 350mA, 500mA & 700mA

Selectable Settings

The ability to select 5 lumen levels without the use of a dimmer

Driver to power Residential Landscape luminaires

98mm

