



DRV3001050

42W CC Driver, IP20, 300-1050mA, Class II SELV Forward voltage range from 9 to 52Vdc

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	45°C
Inrush Current	9A 0.048ms
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (I, 2, 3)	2
Case Temperature (tc = °C)	80
DIN Rail Mount	No
Install Connector Type	Push-fit terminals 0,5 - 1,5mm ²
Connection Output	DC Plug and Play Connector
UK Protection	Open Circuit, Short Circuit, Over Temperature Self Reset
Power Factor	0.95

Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
42	300mA	220-240VAC	300-1050mA	9-52VDC	0.95

ACCESSORIES

Solis	4000K + 5000K LED panel range	Sold Separately
Solis Pro	Highly Efficient 160 Llm/W IP44 Wattage Switchable Product	Sold Separately
Domino	Ultra-low Glare 600x600 Architectural Panel	Sold Separately
Thea Pro Range	High Performance UGR19 (using insert accessory) Downlight	Sold Separately



Reduce lumen output by adjusting current using DIP switches



IP20 Perfect for internal applications



Quick and easy installation with push-fit terminal

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Maximum of 42W

For use with our panels and thea pro range

