

# DOMINO WHITE

Ultra-low Glare 600x600 Architectural Panel

#### **FEATURES**

IP rating	IP40
IK rating	IK08
CSP Switchable	Single CCT
UGR	UGR<16
Sensor Option	On Request
Dimmable Option	Yes (DALI-2, 0-10V, PUSH- DIM)
LED Lifetime	L90 51,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Emergency Option	Yes, using converter

#### INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	-20°C - 40°C		
Weight	3.22kg		
Insulation Coverable	Luminaire: Rolled and blown		
insulation Coverable	insulation Driver: no		
Inrush Current	28A <50ms		
Construction Material	Steel Housing,		
	Polycarbonate Lens		
UK Bathroom Zone	2		
SELV	Yes		
Electric Class (1, 2, 3)	II		
Install Connector Type	2 part first fit connector		
UK Building Regulations	Part P & L		
Mounting Options	Recessed		
TP rating	TP(a)		
Power Factor	0.95		

#### Photometrics @ 25°C

Product Code	Finish	Туре	Beam	W	Colour	lm	lm/W	EM lm	Energy													
DMW66X4K	White RAL9003	Mains	75°	27W	4000K	4350	161	See Accessori es	Å C													
		Non- 03 75° dimmable	700	22W	4000K	3550	161	See Accessori es														
DMW66N4K	White RAL9003			24W	4000K	3850	160	See Accessori es														
DMWOON4K	Wille RALY003		dimmable	dimmable	dimmable	dimmable	dimmable "	dimmable	dimmable	dimmable	dimmable	dimmable	dimmable	dimmable	dimmable	75	25W	4000K	4100	164	See Accessori es	Ġ
				27W	4000K	4350	161	See Accessori es														

## WIRING INFORMATION

Cable / Flying Lead	0.75-1.5mm <sup>2</sup>
Type of Wiring Required	Parallel

# ACCESSORIES

ACCESSORIES		
PS6501100MA	one4all driver DALI-2, Push-dim, 0-10V, 10V PWM	Sold Separately
EUP30T1HMC0	Driver, 30W Panel, TRIAC Mains Dim	Sold Separately
DRV3001050	42W CC Driver, IP20, 300-1050mA, Class II SELV	Sold Separately
LEDEP10	Emergency converte, Self-test & Manual-test switchable	Sold Separately
LEDEP10DA	DALI-2 Emergency Converter 2.5W	Sold Separately
EMRWMAN	Salvus Route White, Man-Test, 120(O) or 130(C) Im	Sold Separately



LIGHTING INNOVATION



UGR16 for office, classroom and retail application



Wattage switchable between 22W, 24W, 25W & 27W



Energy efficient up to 164 Llm/W

## WARRANTY

Warranty 5 year
Battery Warranty 5 year
On-Site Warranty 2 year

## FEATURES & BENEFITS

Perfect for office, classroom and retai application


Differentiate the look of your space with a highquality aesthetic

51,000 hours L90 lifetime

ligh impact rating of IK08

Security cable supplied

RG0 (Risk Exempt) Photo-biological Risk





## LIGHTING INNOVATION

Ultra-low glare UGR16 lighting designed for office, classroom and retail application.

Differentiate the look of your space with a higl quality aesthetic that is not only highly efficier at 160 Llm/W but also rated to IK08.