



SALVUS BULKHEAD

High Output Non-Maintained DALI-2 Bulkhead

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual and DALI-2 Test
Maintained / Non-Maintained	Non-Maintained

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	835g
Inrush Current	4A 1ms
Construction Material	PC Housing
Electric Class (1, 2, 3)	I
Battery	LiFePO4 6.4V 5500mAH
Mounting Options	Surface

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	EM lm	Lx @ 1m
EMBHOWD	White	DALI-2	4	6500K	116	1100	1100	120

WIRING INFORMATION

Type of Wiring Required	Parallel
--------------------------------	----------



LiFePO4 battery



Battery Temperature Monitored



DALI-2 Addressable & Manual Test Option

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

Housing is rugged and made of polycarbonate

Non-Maintained

IP65 suitable for outdoor environments

Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points

345mm

