

SALVUS BULKHEAD

High Output Non-Maintianed Manual and Self Test Bulkhead

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual & Self-Test
Maintained / Non-Maintained	Non-Maintained

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	825g
Inrush Current	4A 1ms
Construction Material	PC Housing
Electric Class (1, 2, 3)	
Battery	LiFePO4 6.4V 5500mAH
Mounting Options	Surface

PHOTOMETRICS @ 25°C

F	Product code	Finish	W	Colour	Beam	lm	EM lm	Lx @ 1m
E	EMBHOWMS	White	4	6500K	116	1100	1100	120

WIRING INFORMATION

Type of Wiring Required Parallel



LIGHTING INNOVATION



LiFePO4 battery



Battery Temperature Monitored



Manual & Self Test Option

WARRANTY

Warranty Battery Warranty 5 years

FEATURES & BENEFITS

ousing is rugged and made of polycarbonate

Non-Maintained

IP65 suitable for outdoor environments

Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points

