

LiFePO4 battery available

Battery Temperature  
Monitored

DALI-2 Addressable

## WARRANTY

Warranty	5 years
Battery Warranty	5 years

## FEATURES & BENEFITS

Compliant with ISO 7010 & 3864

Housing is rugged and made of polycarbonate

Legend Kit included

Self-test function can be easily disabled by  
removing green 2-pin jumper connector



# SALVUS EXIT BLADE

24M Viewing Distance Exit Sign

## FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes
Maintained / Non-Maintained	Maintained

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	EMBLRWDP: 580g, EMBLWDP: 580g
Inrush Current	EMBLRWDP: 4A 1ms, EMBLWDP: 4A 1ms
Cut Out Size	110-115mm
Construction Material	PC Housing
Electric Class (1, 2, 3)	I
Battery	EMBLRWDP: LiFePO4 3.2V 1000mAh, EMBLWDP: LiFePO4 3.2V 1000mAh,
Install Connector Type	Push-fit terminal connector
UK Building Regulations	N/A
Mounting Options	Surface
Viewing distance	24

## PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	EM lm
EMBLRWDP	White	2.5W	6500K	180	34	34

## WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel