



LiFePO4 battery



Battery Temperature
Monitored



DALI-2 Addressable, Manual
& Self Test Option

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

- Compliant with ISO 7010 & 3864
- Housing is rugged and made of polycarbonate
- 6 Possible installation methods with accessories
- Legend Kit included
- Self-test function can be easily disabled by removing green 2-pin jumper connector



SALVUS EXIT SIGN

24M Viewing Distance Exit Sign

FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual & Self-Test
Maintained / Non-Maintained	Maintained

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	765g
Inrush Current	4A 1ms
Construction Material	PC Housing
Electric Class (1, 2, 3)	I
Battery	LiFePO4 3.2V 1000mAH
Install Connector Type	Push-fit terminal connector
UK Building Regulations	N/A
Mounting Options	Surface
Viewing distance	24

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	EM lm
EMBLWMS	White	Manual & Self Test	2.5W	6500K	180	30	30
EMBLWD	White	DALI-2	2.5W	6500K	180	30	30

WIRING INFORMATION

Type of Wiring Required	Parallel
-------------------------	----------

ACCESSORIES

EMBLWRK	Salvus Exit Sign 24M, White Recessing Kit	Sold Separately
EMBLWSK	Salvus Exit Sign 24M, White Susp Kit	Sold Separately
EMBLWSMB	Salvus Exit Sign 24M, White Side Mount Bracket	Sold Separately

