



## SALVUS MAX

High output non-maintained emergency bulkhead

### FEATURES

IP rating	IP66
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Maintained / Non-Maintained	Non-Maintained

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	1.46kg
Inrush Current	6.8A 0.1ms
Construction Material	PC
Electric Class (1, 2, 3)	II
Battery	LiFePO4 6.4V 6.6Ah
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall, BESA & conduit M20

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	EM lm	Lx @ 1m
EMBMAX	White	Manual-test	6W-10W	6500K	135°	1000-1500lm	204-306
EMBMAXST	White	Self-test	6W-10W	6500K	135°	1000-1500lm	204-306

### WIRING INFORMATION

Cable / Flying Lead	0.75-4.0mm <sup>2</sup>
Type of Wiring Required	Parallel

### ACCESSORIES

Area Bay	Use as remote emergency solution to reduce light points required	Sold Separately
Caiman	Use as remote emergency solution to reduce light points required	Sold Separately
Borealis	Use as remote emergency solution to reduce light points required	Sold Separately

**167lm/W** High efficacy of 167lm/W

**W** Wattage Switchable between 6W & 10W

**IP66** IP66 suitable for warehouse all applications

### WARRANTY

Warranty	4 years
Battery Warranty	2 years

### FEATURES & BENEFITS

1500lm output

15 metres mounting height, provides 1 lux (escape route) at floor level when using 29 metre spacings

25 metres mounting height, provides 0.5 (anti-panic) lux at floor level when using 40 metre spacings

Lithium iron phosphate (LiFePO4) battery technology for long lifetime and fast charge times

Captive screws for easy installation

BEAM ANGLE: **135°**

