

SALVUS EXIT BOX

32M Viewing Distance Final Exit Sign

FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual & Self-Test
Maintained / Non-Maintained	Maintained, Non-Maintained
RAL Colour	9016

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	EMBXWMS: 635g, EMBXWD: 635g
Inrush Current	EMBXWMS: 4A 1ms, EMBXWD: 4A 1ms,
Construction Material	Polycarbonate & Steel Housing
Electric Class (1, 2, 3)	I
Battery	EMBXWMS: LiFePO4 3.2V 1000mAH, EMBXWD: LiFePO4 3.2V 1000mAH,
Install Connector Type	Push-fit terminal connector
UK Building Regulations	N/A
Mounting Options	Surface
Viewing distance	32

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	EM lm
EMBXWMS	White	Ceiling Mount Kit	2.5W	6500K	93°	26	26
EMBXWD	White	DALI-2	2.5W	6500K	93°	26	26

WIRING INFORMATION

Type of Wiring Required	Parallel

COLLINGWOOD LIGHTING

LIGHTING INNOVATION

- LiFePO4 battery
- Battery Temperature Monitored
- DALI-2 Addressable, Manual & Self Test Option

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

- Compliant with ISO 7010 & 3864
- Housing is rugged and made of polycarbonate
- Push bar illuminance for final exit
- Legend Kit included
- Self-test function can be easily disabled by removing green 2-pin jumper connector

