SALVUS ROUTE

240lm Surface Anti-panic

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual & Self-Test
Maintained / Non-Maintained	Non-Maintained
RAL Colour	9016

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	EMRSW2MS: 336, EMRSW2D: 292g
Inrush Current	EMRSW2MS: 4A 1ms, EMRSW2D: 4A 1ms
Construction Material	PC Housing
Electric Class (1, 2, 3)	I
Battery	EMERSW2MS: LiFePO4 3.2V 3000mAH, EMERSW2D: LiFePO4 3.2V 3000mAH
Install Connector Type	Push-fit terminal connector
UK Building Regulations	N/A
Mounting Options	Surface

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	EM lm
EMRSW2MS	White	Manual & Self Test	2.5W	6500K	147° (Open Area and Corridor)	240	240
EMRSW2D	White	DALI-2	2.5W	6500K	147° (Open Area and Corridor)	240	240

WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

COLLINGWOOD LIGHTING

LIGHTING INNOVATION

- LiFePO4 battery
- Battery Temperature Monitored
- DALI-2 Addressable, Manual & Self Test Option

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

- Housing is rugged and made of polycarbonate
- Open Area and Corridor lens included
- Simple twist and lock front mechanism to change lenses
- Besa Box footprint and suitable for 20mm conduit entry from side or rear
- Self-test function can be easily disabled by removing green 2-pin jumper connector



