





SALVUS ROUTE

150lm & 300lm Recessed Anti-panic

FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual & Self-Test
Maintained / Non-Maintained	Non-Maintained
RAL Colour	9016

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	EMRW1MS: 270g, EMRW1D:193g, EMRW3MS: 360g, EMRW3D:193g
Inrush Current	EMRW1MS: 4A 1ms, EMRW1D: 4A 1ms, EMRW3MS: 4.2A 1ms, EMRW3D: 4.2A 1ms
Cut Out Size	50
Construction Material	PC Housing
Electric Class (1, 2, 3)	I
Battery	EMRW1MS: LiFePO4 3.2V 2000mAH, EMRW1D: LiFePO4 3.2V 2000mAH, EMRW3MS: LiFePO4 3.2V 5500mAH, EMRW3D: LiFePO4 3.2V 5500mAH
Install Connector Type	Push-fit terminal connector
UK Building Regulations	N/A
Mounting Options	Recessed

WIRING INFORMATION

Type of Wiring Required	Parallel

COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

LiFePO4 battery

Battery Temperature Monitored

DALI-2 Addressable, Manual & Self Test Option

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

Manual and Self Test combined product. Simply remove the green 2-pin jumper connector to set the product to Manual Test

Housing is rugged and made of polycarbonate

Open Area and Corridor lens inlcuded

