





SALVUS ROUTE

150lm & 300lm Recessed Anti-panic

FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual & Self-Test
Maintained / Non-Maintained	Non-Maintained
RAL Colour	9016

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	EMRW1MS: 270g, EMRW1D:193g, EMRW3MS: 360g, EMRW3D:193g
Inrush Current	EMRW1MS: 4A 1ms, EMRW1D: 4A 1ms, EMRW3MS: 4.2A 1ms, EMRW3D: 4.2A 1ms
Cut Out Size	50
Construction Material	PC Housing
Electric Class (1, 2, 3)	I
Battery	EMRW1MS: LiFePO4 3.2V 2000mAH, EMRW1D: LiFePO4 3.2V 2000mAH, EMRW3MS: LiFePO4 3.2V 5500mAH, EMRW3D: LiFePO4 3.2V 5500mAH
Install Connector Type	Push-fit terminal connector
UK Building Regulations	N/A
Mounting Options	Recessed

Area	Mounting Height (m)	Lux level directly under	Spacing (m) between emergency luminaires and walls			
	2.4	17.50	2.08	2.08	2.08	2.08
	2.7	13.83	2.34	2.34	2.34	2.34
	3	11.20	2.60	2.60	2.60	2.60
	3.5	8.23	3.03	3.03	3.03	3.03
	4	6.30	3.47	3.47	3.47	3.47
	4.5	4.98	3.90	3.90	3.90	3.90
	5	4.03	4.33	4.33	4.33	4.33
	6	2.80	5.20	5.20	5.20	5.20
	2.1	1.31	17.23	17.23	17.23	17.23
	2.4	1.00	19.69	19.69	19.69	19.69
	2.7	0.79	22.15	22.15	22.15	22.15
	3	0.64	24.62	24.62	24.62	24.62
	3.5	0.47	28.72	28.72	28.72	28.72
	4	0.36	32.82	32.82	32.82	32.82
	4.5	0.29	36.92	36.92	36.92	36.92
	5.0	0.23	41.03	41.03	41.03	41.03

WIRING INFORMATION

Type of Wiring Required	Parallel

COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

LiFePO4 battery

Battery Temperature Monitored

DALI-2 Addressable, Manual & Self Test Option

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

Manual and Self Test combined product. Simply remove the green 2-pin jumper connector to set the product to Manual Test

Housing is rugged and made of polycarbonate

Open Area and Corridor lens inlcuded



