



Compatible with trailing edge dimmers only

Quick and easy installation with plug and play connector

Ideal for use in indoor applications

EUP30T1HMC0

Panel power supply, IP20, 30W, 750mA, Mains Dimmable

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 50°C
Weight	150g
Insulation Coverable	No
Inrush Current	15A
Construction Material	Plastic
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	2
Install Connector Type	Mains: Push-fit terminals 0.75 - 1.5mm ² DC: Plug & Play connectors
Connection Output	Terminals
Power Factor	0.9

Guarantee

Warranty 3 years

Features & benefits

- IP20 Rated
- 750mA

Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
30W	0.17A	220-240VAC, 50-60Hz	750mA	3-40V DC	0.9

Wiring Information

Input Cable Type	0.75- 2.5mm ²
Output Cable Type	0.75- 2.5mm ²

Accessories

LEDEP10	Emergency converter, Self-test, maintained	Sold Separately
---------	--	-----------------

