

EUP30T1HMC0

Panel power supply, IP20, 30W, 750mA, Mains Dimmable

Features		
IP rating	IP20	
Dimmable Option	Yes (Mains)	

Installation Information			
Input	220-240V AC		
Maximum Ambient Temperature	-20°C - 50°C		
Weight	150g		
Insulation Coverable	No		
Double Insulation	Yes		
Inrush Current	15A		
Construction Material	Plastic		
UK Bathroom Zone	N/A		
SELV	SELV		
Electric Class (1, 2, 3)	2		
	Mains: Push-fit terminals		
Install Connector Type	0.75 - 1.5mm² DC: Plug &		
	Play connectors		
Connection Output	Terminals		
Power Factor	0.9		

Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
30W	0.17A	220-240VAC, 50-60Hz	750mA	3-40V DC	0.9

Wiring Information

Input Cable Type	0.75- 2.5mm²
Output Cable Type	0.75- 2.5mm ²

Accessories

LEDEP10	Emergency converter, Self-test, maintained	Sold Separately



Compatiable with trailing edge dimmers only

Quick and easy installation with plug and play connector

Ideal for use in indoor applications

Guarantee

Warranty 3 years

Features & benefits

- IP20 Rated
- 750mA

