

Compatible with trailing
edge dimmers only

Quick and easy installation
with plug and play
connector

Ideal for use in indoor
applications

WARRANTY

Warranty

3 years

FEATURES & BENEFITS

IP20 Rated

750mA

EUP30T1HMC0

Panel power supply, IP20, 30W, 750mA, Mains Dimmable

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 50°C
Weight	150g
Insulation Coverable	No
Inrush Current	15A
Construction Material	Plastic
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	II
Install Connector Type	Mains: Push-fit terminals 0.75 - 1.5mm ² DC: Plug & Play connectors
Connection Output	Terminals
Power Factor	0.9

Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
30	0.17	220-240VAC, 50-60Hz	750mA	3-40	0.9

WIRING INFORMATION

Input Cable Type	0.75- 2.5mm ²
Output Cable Type	0.75- 2.5mm ²

ACCESSORIES

LEDEP10	Emergency converter, Self-test, maintained	Sold Separately
---------	--	-----------------

