



BOLT-ON EMERGENCY

3 hour emergency conversion pack, rack optic, self or manual test

FEATURES

IP rating	IP65
Emergency Option	Emergency Version

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C to +45°C
Weight	219g
Inrush Current	2A 2.6ms
Construction Material	PC
Electric Class (1, 2, 3)	II
Battery	LiFePO4
Install Connector Type	Flying lead

PHOTOMETRICS @ 25°C

Product code	Finish	Lx @ 1m
EMBOLTRACK	White RAL9016	51
EMBOLSRACK	White RAL9016	51

WIRING INFORMATION

Cable / Flying Lead	1.4m (2x 0.75mm²)
Type of Wiring Required	Parallel

ACCESSORIES

Borealis Batten	All variants	Sold Separately
Caiman Anti Corrosive	All variants	Sold Separately



Self or Manual Test Options



LiFePO4, provides long operational life



A minimum of 3 hours of emergency lighting

WARRANTY

Warranty	4 years
Battery Warranty	2 years

FEATURES & BENEFITS

Compatible with: RackBay Range

Fast 4-minute conversion time

Suitable for use at heights of 2.5 to 6.0 metres

BEAM ANGLE:

