



collingwood

Self or Manual Test Options

M20 interface for easy installation

Lithium iron phosphate battery (LiFePO4)



## Emergency Salvus Bolt-On

### Features

IP rating	IP65
Emergency Option	Emergency Version

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C to +45°C
Weight	219g
Inrush Current	2A 2.6ms
Construction Material	PC
Electric Class (1, 2, 3)	2
Battery	LiFePO4
Install Connector Type	Flying lead

### Guarantee

Warranty	4 years
Battery Warranty	2 years

### Features & benefits

- Compatible with:
- BOREALIS Batten
- CAIMAN Anti-Corrosive
- LENTUS Lowbay
- Suitable for use at heights of 2.5 to 6.0 metres
- Fast 4-minute conversion time

### Photometrics @ 25°C

Product Code	Finish	Type	Lx @ 1m
EMBOLTSCOR	White RAL9016	Non-Maintained Corridor Lens	5l
EMBOLTSOPEN	White RAL9016	Non-Maintained Open Area Lens	5l
EMBOLTMCOR	White RAL9016	Non-Maintained Corridor Lens	5l
EMBOLTMOPEN	White RAL9016	Non-Maintained Open Area Lens	5l

### Wiring Information

Cable / Flying Lead	1.4m (2x 0.75mm <sup>2</sup> )
Type of Wiring Required	Parallel

### Accessories

Borealis Batten	All variants	Sold Separately
Caiman Anti Corrosive	All variants	Sold Separately

