

Self or Manual Test Options

M20 interface for easy
installation

Lithium iron phosphate
battery (LiFePO4)

WARRANTY

Warranty	4 years
Battery Warranty	2 years

FEATURES & BENEFITS

Compatible with:

BOREALIS Batten

CAIMAN Anti-Corrosive

LENTUS Lowbay

Suitable for use at heights of 2.5 to 6.0 metres

Fast 4-minute conversion time



EMERGENCY SALVUS BOLT-ON

3 hour emergency conversion pack

FEATURES

IP rating	IP65
Emergency Option	Emergency Version

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C to +45°C
Weight	219g
Inrush Current	2A 2.6ms
Construction Material	PC
Electric Class (1, 2, 3)	2
Battery	LiFePO4
Install Connector Type	Flying lead

PHOTOMETRICS @ 25°C

Product code	Finish	Type	Lx @ 1m
EMBOLTSOR	White RAL9016	Non-Maintained Corridor Lens	51
EMBOLTSOPEN	White RAL9016	Non-Maintained Open Area Lens	51
EMBOLTMCOR	White RAL9016	Non-Maintained Corridor Lens	51
EMBOLTMOPEN	White RAL9016	Non-Maintained Open Area Lens	51

WIRING INFORMATION

Cable / Flying Lead	1.4m (2x 0.75mm ²)
Type of Wiring Required	Parallel

ACCESSORIES

Borealis Batten	All variants	Sold Separately
Caiman Anti Corrosive	All variants	Sold Separately

