



## Emergency Salvus Bolt-On

3 hour emergency conversion pack

### Features

IP rating	IP65
IK rating	IK07
Sensor Option	No
Colour Rendering Index	CRI>70
Emergency Option	Emergency Version

### Installation Information

Input	220-240V AC
Weight	219g
Inrush Current	2A 2.6ms
Construction Material	PC
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	2
Battery	LiFePO4
Install Connector Type	Flying lead

### Guarantee

Warranty	4 years
Battery Warranty	2 years

### Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	lm	Lx @ 1m
EMBOLTSCOR	White RAL9016	Non-Maintained Corridor Lens	2.5W Max	6000K	200	51
EMBOLTSOPEN	White RAL9016	Non-Maintained Open Area Lens	2.5W Max	6000K	200	51
EMBOLTMCOR	White RAL9016	Non-Maintained Corridor Lens	2.5W Max	6000K	200	51
EMBOLTMOPEN	White RAL9016	Non-Maintained Open Area Lens	2.5W Max	6000K	200	51

### Wiring Information

Cable / Flying Lead	1.4m (2x 0.75mm <sup>2</sup> )
Type of Wiring Required	Parallel

### Accessories

Borealis Batten	All variants	Sold Separately
Caiman Anti Corrosive	All variants	Sold Separately
Lentus Lowbay	All variants	Sold Separately

### Features & benefits

- Compatible with:
- BOREALIS Batten
- CAIMAN Anti-Corrosive
- LENTUS Lowbay
- Suitable for use at heights of 2.5 to 6.0 metres
- Fast 4-minute conversion time
- M20 interface for easy installation
- Lithium iron phosphate battery (LiFePO4)

