



- 118lm/W** High efficacy of up to 118lm/W
- First fix bracket for quick & easy installation
- Ideal for coastal areas

## FL10

100W colour switchable floodlight

### FEATURES

IP rating	IP65
IK rating	IK07
CSP Switchable	Switchable CCT
Tiltable (°)	180
UGR	UGR<16
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Rotation angle (°)	360

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 40°C
Weight	2100g
Inrush Current	75A 5ms
Construction Material	Black painted cast aluminium
Electric Class (1, 2, 3)	I
Earth Leakage	0.3
Suitable for coastal areas	Yes
Install Connector Type	Flying lead
UK Building Regulations	N/A
Mounting Options	Wall
Power Factor	0.9

### Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	lx@1m	Energy
FL10BXC5	Black	Standard	120°	100W	3000K	10250	103	4275	
					4000K	11810	118	4926	
					6500K	10970	110	4575	

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable 3x1.0mm² Ø7mm
Type of Wiring Required	Parallel
Input Cable Type	3x 1.0mm²

### ACCESSORIES

N/A (No Accessories required)
-------------------------------

### WARRANTY

Warranty 5 years

### FEATURES & BENEFITS

Colour switchable between 3 colour temperatures

IP65 rated, meaning it provides optimum protection against the impacts of rainwater and general adverse weather conditions

A unique 360° rotation for total flexibility, and a 180° tilt

Supplied with 1m cable

Wide 120° beam angle, reducing the number of fittings per area required

Performs in even more extreme conditions from -40°C to +40°C

BEAM ANGLE: **120°**

