



- IP68** IP68 suitable for full submersion into water
- IK08** IK08 for protection against high impact
- Suitable for coastal C5 and high acid and alkali environment

Fountain

Water feature light

Features

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	24V DC
Maximum Ambient Temperature	-25°C - 40°C
Weight	2.58kg
Inrush Current	N/A
Cut Out Size	167
Construction Material	316 Stainless Steel
UK Bathroom Zone	0, 1 (with dimming)
SELV	SELV
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes
Install Connector Type	Flying lead
Mounting Options	1 1/2" BSP thread

Guarantee

Warranty 5 years

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
FOUX167N30	Stainless steel 316	35°	25W	3000K	1700	68	4057	

Wiring Information

Cable / Flying Lead	Pre-wired 5.0M H05RN-F, 2x1.0mm2
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PS5024	220-240V	Yes	No	0	1	2
LSDI2024	220-240V	Yes	No	0	1	4
PSIP25024	220-240V	Yes	No	0	1	10

Accessories

JB5	Gel filled waterproof connector	Sold Separately
-----	---------------------------------	-----------------

Features & benefits

- 316 Stainless steel housing and titanium cover provides outstanding corrosion resistance
- Clear but strong 8mm tempered glass cover provides high efficiency and clear colour accuracy
- TRIAC mains dimmable as standard with RGBW option
- Pre-wired with 5 metres of cable to aid the installer
- To be installed under water to prevent over-heating
- 1 1/2" BSP thread enables installation onto fabricated pipework
- RGBW version available

Beam angle: 35°

