



RGBW



IP68 suitable for full submersion into water



Suitable for coastal C5 and high acid and alkali environment

## Fountain RGBW

Water feature light

### Features

IP rating	IP68
IK rating	IK08
CSP Switchable	RGBW
Dimmable Option	Yes
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel Only)

### Installation Information

Input	600mA
Maximum Ambient Temperature	-25°C - 40°C
Weight	2.58kg
Inrush Current	N/A
Cut Out Size	167
Construction Material	316 Stainless Steel
UK Bathroom Zone	0, 1 (with dimming)
SELV	Yes
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes
Install Connector Type	Flying lead
Mounting Options	1 1/2" BSP thread

### Guarantee

Warranty 5 years

### Features & benefits

- 316 Stainless steel housing and titanium cover provides outstanding corrosion resistance
- Clear but strong 8mm tempered glass cover provides high efficiency and clear colour accuracy
- TRIAC mains dimmable as standard with RGBW option
- Pre-wired with 5 metres of cable to aid the installer
- To be installed under water to prevent over-heating
- 1 1/2" BSP thread enables installation onto fabricated pipework
- 24V version available

### RGBW Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
FOUX167RGBW	13W	White (3000K)	35°	350	40	1140
FOUX167RGBW	10W	Red	35°	500	40	1629
FOUX167RGBW	13W	Green	35°	200	15	652
FOUX167RGBW	13W	Blue	35°	500	35	1629

Energy rating is a reflection of the LED light source.

### Wiring Information

Cable / Flying Lead	Pre-wired 5.0M H05RN-F, 2x1.0mm <sup>2</sup>
Type of Wiring Required	Series

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	1
CCDRV75DMX	220-240V	Yes	Yes	2	1
CCDRV75RF	220-240V	Yes	Yes	2	1

### Accessories

JB7	5 pole screw terminal IP68 connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately

### Beam angle: 35°

