



GL016 F AB

1W, 95lm ground light

FEATURES

IP rating	IP68
IK rating	IK07
CSP Switchable	Single CCT
Tiltable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	No

INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	50°C
Weight	400g
Inrush Current	N/A
Cut Out Size	50
Construction Material	Brass
UK Bathroom Zone	0
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
GL016 F AB NW	Brass	26°	1W (350mA)	4000K	95	95	267	A to G: F
			2W (700mA)	4000K	140	70	267	
GL016 F AB WW	Brass	26°	1W (350mA)	3000K	75	75	210	A to G: F
			2W (700mA)	3000K	135	68	210	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP70018W	220-240V	Yes	No	0	1	8

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/50	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

COLLINGWOOD LIGHTING

LIGHTING INNOVATION

1W at 350mA or 2W at 700mA

Solid brass with antique effect for low glare

Low voltage ground light

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

- Robust cable for outdoor use
- Shallow depth for easy installation
- Coastal protected

BEAM ANGLE: **26°**



