



collingwood

1W at 350mA or 2W at 700mA

Solid brass with antique effect for low glare

Low voltage ground light

GL016 F AB

1W, 95lm ground light

Features

| | |
|------------------------|-------------|
| IP rating | IP68 |
| IK rating | IK09 |
| CSP Switchable | Single CCT |
| LED Lifetime | L70 70,000h |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | Walk over |

Installation Information

| | |
|-----------------------------|---------------|
| Input | 350mA / 700mA |
| Maximum Ambient Temperature | 50°C |
| Weight | 400g |
| Cut Out Size | Ø 50mm |
| Construction Material | Brass |
| UK Bathroom Zone | 0 |
| Electric Class (1, 2, 3) | 3 |
| Suitable for coastal areas | Yes |

Guarantee

Features & benefits

- Robust cable for outdoor use
- Shallow depth for easy installation
- Coastal protected

Photometrics @ 25°C

| Product Code | Finish | Colour | Beam | 350mA | | | | 700mA | | | | Energy |
|---------------|--------|--------|------|-------|----|------|---------|-------|-----|------|---------|--------|
| | | | | W | lm | lm/W | Ix @ 1m | W | lm | lm/W | Ix @ 1m | |
| GL016 F AB NW | Brass | 4000K | 26° | 1W | 95 | 95 | 267 | 2W | 140 | 70 | 393 | AG F |
| GL016 F AB WW | Brass | 3000K | 26° | 1W | 75 | 75 | 210 | 2W | 135 | 68 | 379 | AG F |
| GL016 F AB 27 | Brass | 2700K | 26° | 1W | 70 | 70 | 196 | 2W | 120 | 60 | 337 | AG F |

Wiring Information

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |
| Input Cable Type | H05RN-F (6MM OD) 2 CORE |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|---------------------|----------|------|-------------|---------------|-----|-----|
| PLR/350 1-5 | 220-240V | Yes | No | 0 | 1 | 5 |
| PLD UNI-DRIVE 350MA | | Yes | Yes (1-10V) | 2 | 1 | 10 |
| PLU/700 3-9 | | Yes | No | 1 | 3 | 9 |

Accessories

| | |
|-----------------|--|
| JB2 / JB4 / JB6 | IP68 waterproof connectors |
| TUBE/50 | Installation tube |
| WCR 275 BLACK | 2-core rubber cable |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types |

