



collingwood

1W at 350mA or 2W at 700mA

Solid brass with antique effect for low glare

Low voltage ground light

GL016 F AB

1W, 95lm ground light

Features

IP rating	IP68
IK rating	IK09
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	50°C
Weight	400g
Cut Out Size	Ø 50mm
Construction Material	Brass
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

Guarantee

Features & benefits

- Robust cable for outdoor use
- Shallow depth for easy installation
- Coastal protected

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	350mA				700mA				Energy
				W	lm	lm/W	Ix @ 1m	W	lm	lm/W	Ix @ 1m	
GL016 F AB NW	Brass	4000K	26°	1W	95	95	267	2W	140	70	393	A G F
GL016 F AB WW	Brass	3000K	26°	1W	75	75	210	2W	135	68	379	A G F
GL016 F AB 27	Brass	2700K	26°	1W	70	70	196	2W	120	60	337	A G F

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLR/350 1-5	220-240V	Yes	No	0	1	5
PLD UNI-DRIVE 350MA		Yes	Yes (1-10V)	2	1	10
PLU/700 3-9		Yes	No	1	3	9

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE/50	Installation tube
WCR 275 BLACK	2-core rubber cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types

