

1W at 350mA or 2W at
700mA

Solid brass with antique
effect for low glare

Low voltage ground light

FEATURES & BENEFITS

Robust cable for outdoor use

Shallow depth for easy installation

Coastal protected



GL016 F AB

1W, 95lm ground light

FEATURES

IP rating	IP68
IK rating	IK09
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	50°C
Weight	400g
Cut Out Size	Ø 50mm
Construction Material	Brass
UK Bathroom Zone	0
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
GL016 F AB NW	Brass	26°	1W (350mA)	4000K	95	95	267	
			2W (700mA)	4000K	140	70	267	
GL016 F AB WW	Brass	26°	1W (350mA)	3000K	75	75	210	
			2W (700mA)	3000K	135	68	210	

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLR/350 1-5	220-240V	Yes	No	0	1	5
PLD UNI-DRIVE 350MA		Yes	Yes (1-10V)	2	1	10
PLU/700 3-9		Yes	No	1	3	9

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE/50	Installation tube
WCR 275 BLACK	2-core rubber cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types

26°