

1W at 350mA or 2W at
700mA

Coastal protected

Low voltage ground light

FEATURES & BENEFITS

Robust cable for outdoor use

Shallow depth for easy installation



GL016 F

1W, 95lm ground light

FEATURES

| | |
|-------------------------------|-------------|
| IP rating | IP68 |
| IK rating | IK09 |
| CSP Switchable | Single CCT |
| LED Lifetime | L70 70,000h |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | Walk over |

INSTALLATION INFORMATION

| | |
|------------------------------------|-----------------------|
| Input | 350mA / 700mA DC |
| Maximum Ambient Temperature | 50°C |
| Weight | 400g |
| Cut Out Size | Ø 50mm |
| Construction Material | Stainless steel (316) |
| UK Bathroom Zone | 0 |
| Electric Class (1, 2, 3) | III |
| Suitable for coastal areas | Yes |

Photometrics @ 25°C

| Product Code | Finish | Beam | W | Colour | lm | lm/W | lx@1m | Energy |
|---------------------|---------------|------|------------|--------|-----|------|-------|--------|
| GL016 F NW | Brushed steel | 26° | 1W (350mA) | 4000K | 95 | 95 | 267 | |
| | | | 2W (700mA) | 4000K | 140 | 70 | 267 | |
| GL016 F 27 | Brushed steel | 26° | 1W (350mA) | 2700K | 70 | 70 | 196 | |
| | | | 2W (700mA) | 2700K | 120 | 60 | 196 | |
| GL016 F BLUE | Brushed steel | 26° | 1W (350mA) | Blue | 10 | 10 | 28 | |
| | | | 2W (700mA) | Blue | 20 | 10 | 28 | |
| GL016BMBX40 | Black | 26° | 1W (350mA) | 4000K | 95 | 95 | 267 | |
| | | | 2W (700mA) | 4000K | 140 | 70 | 267 | |
| GL016BMBXBL | Black | 26° | 1W (350mA) | Blue | 20 | 20 | 28 | |
| | | | 2W (700mA) | Blue | 20 | 10 | 28 | |

26°

WIRING INFORMATION

| | |
|--------------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |
| Input Cable Type | H05RN-F (6MM OD) 2 CORE |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|---------------------|----------|------|-------------|---------------|-----|-----|
| PLU/350 1-9 | 220-240V | Yes | No | 1 | 1 | 9 |
| PLD UNI-DRIVE 350MA | | Yes | Yes (1-10V) | 2 | 1 | 10 |
| PLU/700 3-9 | | Yes | No | 1 | 3 | 9 |

ACCESSORIES

| | |
|------------------------|--|
| JB2 / JB4 / JB6 | IP68 waterproof connectors |
| TUBE/50 | Installation tube |
| WCR 275 BLACK | 2-core rubber cable |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types |