

1W

1W at 350mA or 2W at 700mA



Frosted effect for low glare and soft lighting



Low voltage ground light

## WARRANTY

Warranty

7 years

## FEATURES & BENEFITS

Robust cable for outdoor use

Shallow depth for easy installation

Marine-grade stainless steel 316 or Black anodised aluminium

## GL016 FROSTED

1W, 15lm ground marker light

### FEATURES

|                        |  |
|------------------------|--|
| IP rating              | IP68   |
| IK rating              | IK07   |
| CSP Switchable         | Single CCT                                       |
| Tiltable               | No   |
| LED Lifetime           | L70 70,000h                                      |
| Colour Rendering Index | CRI>80   |
| Colour Consistency     | SDCM3  |
| Walk Over / Drive Over | Walk over (Stainless Steel & Antique Brass Only) |

### INSTALLATION INFORMATION

|                             |                       |
|-----------------------------|-----------------------|
| Input                       | 350mA / 700mA         |
| Maximum Ambient Temperature | 50°C                  |
| Weight                      | 400g                  |
| Inrush Current              | N/A                   |
| Cut Out Size                | 50                    |
| Construction Material       | Stainless steel (316) |
| UK Bathroom Zone            | 0                     |
| SELV                        | Yes                   |
| Electric Class (1, 2, 3)    | 3                     |
| Earth Leakage               | N/A                   |
| Suitable for coastal areas  | Yes                   |

### Photometrics @ 25°C

| Product Code | Finish          | Beam | W          | Colour | lm | lm/W | lx@1m | Energy |
|--------------|-----------------|------|------------|--------|----|------|-------|--------|
| GL016DC0F40  | Stainless steel | 100° | 1W (350mA) | 4000K  | 15 | 15   | 5     |        |
| GL016DC0F30  | Stainless steel | 100° | 1W (350mA) | 3000K  | 13 | 13   | 5     |        |
| GL016DC0F27  | Stainless steel | 100° | 1W (350mA) | 2700K  | 12 | 12   | 4     |        |
| GL016BC0F27  | Black           | 100° | 1W (350mA) | 2700K  | 12 | 12   | 4     |        |
| GL016BC0F30  | Black           | 100° | 1W (350mA) | 3000K  | 13 | 13   | 5     |        |
| GL016BC0F40  | Black           | 100° | 1W (350mA) | 4000K  | 15 | 15   | 5     |        |

### WIRING INFORMATION

|                         |   |
|-------------------------|---|
| Cable / Flying Lead     | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series  |
| Input Cable Type        | H05RN-F (6MM OD) 2 CORE                               |

### LED DRIVER

| Driver     | Input    | SELV | Dimming | Bathroom Zone | Min | Max |
|------------|----------|------|---------|---------------|-----|-----|
| PSIP70018W | 220-240V | Yes  | No      | 0             | 1   | 8   |

### ACCESSORIES

|                 |  |                 |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | IP68 waterproof connectors                 | Sold Separately |
| TUBE/50         | Installation tube                          | Sold Separately |
| WCR 275 BLACK   | 2-core rubber cable                        | Sold Separately |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types | Sold Separately |

