



- 1W** 1W at 350mA or 2W at 700mA
- Frosted effect** for low glare and soft lighting
- DC** Low voltage ground light

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

- Robust cable for outdoor use
- Shallow depth for easy installation
- Marine-grade stainless steel 316 or Black anodised aluminium

GL016 FROSTED

1W, 15lm ground marker light

FEATURES

IP rating	IP68
IK rating	IK07
CSP Switchable	Single CCT
Tiltable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	50°C
Weight	400g
Inrush Current	N/A
Cut Out Size	50
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
SELV	Yes
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
GL016DC0F40	Stainless steel	100°	1W (350mA)	4000K	15	15	5	
GL016DC0F30	Stainless steel	100°	1W (350mA)	3000K	13	13	5	
GL016DC0F27	Stainless steel	100°	1W (350mA)	2700K	12	12	4	
GL016BC0F27	Black	100°	1W (350mA)	2700K	12	12	4	
GL016BC0F30	Black	100°	1W (350mA)	3000K	13	13	5	
GL016BC0F40	Black	100°	1W (350mA)	4000K	15	15	5	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP70018W	220-240V	Yes	No	0	1	8

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/50	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

BEAM ANGLE: **100°**

