



RGBW



Coastal protected



IK08 suitable for pathways

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Installation tube available

Low profile for easy installation

Separate white LED for permanent use

Compatible with a large range of controllers

Marine grade stainless steel for use in outdoor and indoor environments

GL016RGBW

LED colour change ground light (5W max.)

FEATURES

IP rating	IP67
IK rating	IK07
CSP Switchable	RGBW
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel Only)

INSTALLATION INFORMATION

Input	350mA
Maximum Ambient Temperature	35°C
Weight	300g
Cut Out Size	50
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

RGBW Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
GL016RGBW	1.2W	White (4000K)	40°	50	42	74
GL016RGBW	1W	Red	40°	38	38	75
GL016RGBW	1.2W	Green	40°	63	53	124
GL016RGBW	1.2W	Blue	40°	11	9	17

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F 5 CORE, 8MM OD

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	13
CCDRV75DMX	220-240V	Yes	Yes	2	13
CCDRV75RF	220-240V	Yes	Yes	2	13

ACCESSORIES

JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
TUBE/50	Installation tube	Sold Separately
CCRCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately

BEAM ANGLE: 40°

