



GL016RGBW

LED colour change ground light (5W max.)

FEATURES

IP rating	IP67
IK rating	IK07
CSP Switchable	RGBW
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel Only)

INSTALLATION INFORMATION

Input	350mA
Maximum Ambient Temperature	35°C
Weight	300g
Cut Out Size	50
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

RGBW Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
GL016RGBW	1.2W	White (4000K)	40°	50	42	74
GL016RGBW	1W	Red	40°	38	38	75
GL016RGBW	1.2W	Green	40°	63	53	124
GL016RGBW	1.2W	Blue	40°	11	9	17

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F 5 CORE, 8MM OD

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	13
CCDRV75DMX	220-240V	Yes	Yes	2	13
CCDRV75RF	220-240V	Yes	Yes	2	13

ACCESSORIES

JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
TUBE/50	Installation tube	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately



RGBW



Coastal protected



IK08 suitable for pathways

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Installation tube available

Low profile for easy installation

Separate white LED for permanent use

Compatible with a large range of controllers

Marine grade stainless steel for use in outdoor and indoor environments

BEAM ANGLE: **40°**

