

0.5W at 24V DC

Frosted effect for low glare and soft lighting

Low voltage ground light

## FEATURES & BENEFITS

Solid brass with antique effect

Robust cable for outdoor use

Shallow depth for easy installation

Easy and quick installation with parallel wiring



## GL018 C AB

mini antique brass marker ground light

### FEATURES

<b>IP rating</b>	IP68
<b>IK rating</b>	IK07
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 30,000h
<b>Colour Consistency</b>	SDCM3
<b>Walk Over / Drive Over</b>	Walk over

### INSTALLATION INFORMATION

<b>Input</b>	24V DC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	300g
<b>Cut Out Size</b>	Ø 28mm
<b>Construction Material</b>	Brass
<b>UK Bathroom Zone</b>	0
<b>Electric Class (1, 2, 3)</b>	III
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m
GL018 C AB NW	Antique brass	0.5W	4000K	120°	3	6	1
GL018 C AB WW	Antique brass	0.4W	3000K	120°	4	10	1
GL018 C AB 27	Antique brass	0.5W	2700K	120°	3	6	1
GL018 C AB BLUE	Antique brass	0.5W	Blue	120°	0.5	1.3	0.18

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Parallel
<b>Input Cable Type</b>	H05RN-F (6MM OD) 2 CORE

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PS1524	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	30
PS5024		Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	100
PSDIP10024		Yes	Yes (1-10V)	0 (1 when dimming)	1	200

### ACCESSORIES

<b>JB1 / JB5 / JB6</b>	IP68 waterproof connectors
<b>PDC/GRID DIMMER</b>	Grid dimmer kit for multiple fitting types
<b>PDCINT1-10V</b>	1-10V dimming interface for use with 24V LED drivers

120°