



GL018 C AB

mini antique brass marker ground light

FEATURES

IP rating	IP68
IK rating	IK07
CSP Switchable	Single CCT
LED Lifetime	L70 30,000h
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	24V DC
Maximum Ambient Temperature	35°C
Weight	300g
Cut Out Size	Ø 28mm
Construction Material	Brass
UK Bathroom Zone	0
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m
GL018 C AB NW	Antique brass	0.5W	4000K	120°	3	6	1
GL018 C AB WW	Antique brass	0.4W	3000K	120°	4	10	1
GL018 C AB 27	Antique brass	0.5W	2700K	120°	3	6	1
GL018 C AB BLUE	Antique brass	0.5W	Blue	120°	0.5	1.3	0.18

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSI524	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	30
PS5024		Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	100
PSDIP10024		Yes	Yes (1-10V)	0 (1 when dimming)	1	200

ACCESSORIES

JB1 / JB5 / JB6	IP68 waterproof connectors
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers

FEATURES & BENEFITS

- Solid brass with antique effect
- Robust cable for outdoor use
- Shallow depth for easy installation
- Easy and quick installation with parallel wiring