



1W at 350mA or 2W at 700mA



Coastal protected

Low voltage step light

## GL019 Eyelid

Asymmetric beam angle with zero upward light spill

### Features

|                        |             |
|------------------------|-------------|
| IP rating              | IP68        |
| IK rating              | N/A         |
| CSP Switchable         | Single CCT  |
| LED Lifetime           | L70 70,000h |
| Colour Rendering Index | CRI>80      |
| Colour Consistency     | SDCM3       |
| Walk Over / Drive Over | No          |

### Installation Information

|                             |                       |
|-----------------------------|-----------------------|
| Input                       | 350mA / 700mA         |
| Maximum Ambient Temperature | 50°C                  |
| Weight                      | 204g                  |
| Inrush Current              | N/A                   |
| Cut Out Size                | 33                    |
| Construction Material       | Stainless steel (316) |
| UK Bathroom Zone            | 0                     |
| SELV                        | N/A                   |
| Electric Class (1, 2, 3)    | 3                     |
| Earth Leakage               | N/A                   |
| Suitable for coastal areas  | Yes                   |
| Mounting Options            | Recessed              |

### Guarantee

Warranty 7 years

### Features & benefits

- Asymmetric beam angle
- 0% upward light spill
- Recess into a wall, floor or ceiling
- Suitable for indoor and outdoor use
- 33mm cut-out size

### Patent Information

GB2544975 EP3176502

### Photometrics @ 25°C

| Product Code | Finish          | Beam | W          | Colour | lm | lm/W | lx@1m | Energy |
|--------------|-----------------|------|------------|--------|----|------|-------|--------|
| GL019E30SS   | Stainless steel | 50°  | 1W (350mA) | 3000K  | 41 | 41   | 3.5   |        |
|              |                 |      | 2W (700mA) | 3000K  | 72 | 36   | 3.5   |        |
| GL019E27SS   | Stainless steel | 50°  | 1W (350mA) | 2700K  | 36 | 36   | 3.1   |        |
|              |                 |      | 2W (700mA) | 2700K  | 63 | 31   | 3.1   |        |
| GL019E30BL   | Black           | 50°  | 1W (350mA) | 3000K  | 36 | 36   | 2.1   |        |
|              |                 |      | 2W (700mA) | 3000K  | 64 | 32   | 2.1   |        |
| GL019E27BL   | Black           | 50°  | 1W (350mA) | 2700K  | 31 | 31   | 1.8   |        |
|              |                 |      | 2W (700mA) | 2700K  | 56 | 28   | 1.8   |        |

### Wiring Information

|                         |   |
|-------------------------|---|
| Cable / Flying Lead     | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series  |

### LED Driver

| Driver                   | Input    | SELV | Dimming | Bathroom Zone | Min | Max |
|--------------------------|----------|------|---------|---------------|-----|-----|
| DRV150700 (all settings) | 220-240V | Yes  | No      | N/A           |     |     |
| DRV350700TD (700mA)      | 220-240V | Yes  | Yes     | N/A           |     |     |
| PSIP70018W               | 220-240V | Yes  | No      | 0             | 1   | 8   |

### Accessories

|                 |                            |                 |
|-----------------|----------------------------|-----------------|
| JB2 / JB4 / JB6 | IP68 waterproof connectors | Sold Separately |
| TUBE332         | Installation tube          | Sold Separately |

