



1W at 350mA or 2W at 700mA



Coastal protected

Low voltage step light

GL019 Eyelid

Asymmetric beam angle with zero upward light spill

Features

IP rating	IP68
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	No

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	50°C
Weight	204g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes
Mounting Options	Recessed

Guarantee

Warranty 7 years

Features & benefits

- Asymmetric beam angle
- 0% upward light spill
- Recess into a wall, floor or ceiling
- Suitable for indoor and outdoor use
- 33mm cut-out size

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	350mA				700mA				Energy
				W	lm	lm/W	lx@ 1m	W	lm	lm/W	lx@ 1m	
GL019E30SS	Stainless steel	3000K	50°	1W	41	41	3.5	2W	72	36	6	
GL019E27SS	Stainless steel	2700K	50°	1W	36	36	3.1	2W	63	31	5	
GL019E30BL	Black	3000K	50°	1W	36	36	2.1	2W	64	32	3.8	
GL019E27BL	Black	2700K	50°	1W	31	31	1.8	2W	56	28	3.3	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

