



1W at 350mA or 2W at 700mA



Coastal protected

Low voltage step light

GL019 Eyelid

Features

IP rating	IP68
IK rating	N/A
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	No

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	50°C
Weight	204g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
SELV	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes
Mounting Options	Recessed

Guarantee

Warranty 7 years

Features & benefits

- Asymmetric beam angle
- 0% upward light spill
- Recess into a wall, floor or ceiling
- Suitable for indoor and outdoor use
- 33mm cut-out size

Patent Information

GB2544975 EP3176502

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
GL019E30SS	Stainless steel	50°	1W (350mA)	3000K	41	41	3.5	
			2W (700mA)	3000K	72	36	3.5	
GL019E27SS	Stainless steel	50°	1W (350mA)	2700K	36	36	3.1	
			2W (700mA)	2700K	63	31	3.1	
GL019E30BL	Black	50°	1W (350mA)	3000K	36	36	2.1	
			2W (700mA)	3000K	64	32	2.1	
GL019E27BL	Black	50°	1W (350mA)	2700K	31	31	1.8	
			2W (700mA)	2700K	56	28	1.8	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700 (all settings)	220-240V	Yes	No	N/A		
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A		
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately

