



1W at 350mA or 2W at 700mA



Frosted effect for low glare and soft lighting

Low voltage ground light

GL019 Frosted

1W, 13lm frosted mini ground light

Features

| | |
|------------------------|-------------|
| IP rating | IP68 |
| IK rating | IK07 |
| CSP Switchable | Single CCT |
| LED Lifetime | L70 70,000h |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | Walk over |

Installation Information

| | |
|-----------------------------|-----------------------|
| Input | 350mA / 700mA |
| Maximum Ambient Temperature | 50°C |
| Weight | 196g |
| Inrush Current | N/A |
| Cut Out Size | 33 |
| Construction Material | Stainless steel (316) |
| UK Bathroom Zone | 0 |
| Electric Class (1, 2, 3) | 3 |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

Guarantee

Warranty 7 years

Features & benefits

- Robust cable for outdoor use
- Shallow depth for easy installation

Photometrics @ 25°C

| Product Code | Finish | Colour | Beam | 350mA | | | | 700mA | |
|--------------|-----------------|--------|------|-------|----|------|---------|-------|--------|
| | | | | W | lm | lm/W | lx @ 1m | W | Energy |
| GL019DC0F40 | Stainless steel | 4000K | 100° | 1W | 13 | 13 | 5 | | |
| GL019DC0F30 | Stainless steel | 3000K | 100° | 1W | 11 | 11 | 4 | | |
| GL019DC0F27 | Stainless steel | 2700K | 100° | 1W | 10 | 10 | 4 | | |
| GL019DC0FBL | Stainless steel | Blue | 100° | 1W | 2 | 2 | | | |
| GL019BC0F27 | Black | 2700K | 100° | 1W | 10 | 10 | 4 | 2W | |
| GL019BC0F30 | Black | 3000K | 100° | 1W | 11 | 11 | 4 | 2W | |
| GL019BC0F40 | Black | 4000K | 100° | 1W | 13 | 13 | 5 | 2W | |

Wiring Information

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|-------------|----------|------|---------|---------------|-----|-----|
| PLU/350 1-9 | 220-240V | Yes | No | 0 | 1 | 9 |
| PLU/700 3-9 | 220-240V | Yes | No | 0 | 3 | 9 |
| PSIP70018W | 220-240V | Yes | No | 0 | 1 | 8 |

Accessories

| | | |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | IP68 waterproof connectors | Sold Separately |
| TUBE332 | Installation tube | Sold Separately |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types | Sold Separately |

